

## INDUSTRIAL GRADE MODEMS

### Hidex II V.92, 56Kbps

Model: HXII56TM

#### KEY FEATURES

- Call back security
- Dial up phone lines up to 56Kbps
- 2 Wire leased line
- HX Telco line surge protection
- -40°C to +85°C Operating Temp
- DB 25pin data connector
- Global Compliance
- Telecom approved in over 50 countries
- V.44 & V.42bis data compression
- V.42 Error correction
- Intelligent DAA detects line status
- Low power/sleep mode
- Fast POS V.29 & V.22bis Fast connect
- Extended AT Commands & NVRAM
- Native supply voltage is 5VDC
- Optional DC power models 9-18, 18-36, 36-72 or 125-240 AC or DC
- Selectable power via RS232 connector
- Metal case with mounting tabs



#### DESCRIPTION

The **Raymar-Telenetics** Hidex II V.92 Industrial Grade Modem is the most versatile model for dial up or leased analog telephone line interconnect. The Hidex HXII56TM offers up to 56K dial up. They are temperature tested, rugged modems designed for Industrial applications. Directly connected to RTU's, traffic controllers, variable message signs or any number or other applications, they communicate at 300bps to 56Kbps over analog telephone lines. All HX models have high voltage surge protection on the telephone lines. The AC power converter delivers 5VDC from 100 to 120VAC, 50-60Hz with World Wide safety approvals and a locking connector to prevent vibration disconnects. A wide voltage range of internal DC power models are optional. Specify your choice of 9 to 72VDC or external 125 to 240VDC adapter.



Power Adapter and connector

#### RAYMAR INFORMATION TECHNOLOGY, INC.

7325 Roseville Road  
Sacramento, CA 95842  
USA

+1-916-783-1951  
FAX +1-916-783-1952

sales@raymarinc.com

1-800-695-1951

Tech Support Hotline  
1-800-747-1522

www.raymarinc.com

# INDUSTRIAL GRADE MODEMS • HIDEX II V.92, 56Kbps • MODEL: HXII56TM

## TECHNICAL SPECIFICATIONS

Category	Description
Client-to Server Data Rates	Supports V.92 and V.90 data rates
AGC Dynamic Range	43 dB
Data Rates	56,000, 33,600, 31,200, 28,800, 26,400, 24,000, 21,600, 19,200, 16,800, 14,400, 12,000, 9,600, 7,200, 4,800, 2,400, 1,200, 0-300 bps
Command Buffer	60 Characters
DAA Isolation	1500 VAC
Data Compatibility	V.92, V.34 enhanced, V.34, V.32bis, V.22bis, V.22, Bell 212A and 103/113, V.21 & V.23
Data Compression	ITU-T V.44 (6:1 throughput), V.42bis (4:1 throughput), MNP 5 (2:1 throughput)
Fax Compression	MH, MR, MMR
Data Format	Serial, binary, asynchronous (available with parallel interface)
Diagnostics	Local analog loop, local digital loop, remote digital loop
Dimensions	5 x 3 x 1 inches plus mounting tabs
Case material	Black zinc oxide plated steel
Error Correction	Data Mode: V.42 (LAP-M or MNP 3-4)
Fax Compatibility	ITU-T "Super" Group 3, Class 1.0 (2.0, 2.1 - V.92 build only), Group3, Class 1 & 2, T.4 T.30 Annex A & C, V.21, V.27ter, V.29, V.34, V.17, and TIA/EIA TR29.2 V.34 Super G3 fax at speeds up to 33.6Kbps V.17 G3 fax at speeds up to 14.4Kbps
Fax mode error correction	T.30 Annex A & C
Fax Data Rates	33,600, 31,200, 28,800, 26,400, 2400, 21,600, 19,200, 16,800, 14,400, 12,00, 9,600, 7,200, 4,800, 2,400, 1,200, 0-300 bps
Flow Control	XON/XOFF (software), RTS/CTS (hardware)
Operational Temperature	Typical: TBD Standby or Sleep Mode: TBD Maximum: TBD
Receiver Sensitivity	-43 dBm under worst case conditions
Serial Speeds	Serial port data rates adjustable to 300, 1,200, 2,400, 2,400, 4,800, 9,600, 19,200, 38,400, 57,600, 115,200, and 230,400 bps
Storage Temperature	-50° to +100°C
Registration No.	AU7USA-25814-M5-E
Ringer Equivalence	0.3B
Modular Jack (USOC)	RJ11
Approvals	Safety Certifications UL1950, UL60950, CUL60950, EN60950, IEC60950, ACA TS001 / AS 3260, CCC
EMC Approvals	FCC Part 5, Canadian EMC, EN 55022, EN 55024, GB4943, GB9254
Intelligent Features	Fully AT command compatible, Leased line operation, Sleep Mode, Autodial, Redial, Pulse or tone dial, Dial pauses, Auto answer, Adaptive line probing, Automatic symbol and carrier frequency during start up, retrain and rate renegotiations. DTMF detection, Distinctive ring, Call status display, Auto parity and data rate selections Keyboard controlled modem options, On screen displays for modem option parameters, Remote configuration, DTR dialing, Phone number storage, flash memory for firmware updates, NVRAM storage for user define

### Order Information

IGM-HXII33TM	V.34, 33.6K, -40 +85C, 5 VDC
IGM-HXII33TM-A	V.34, 33.6K, -40 +85C, 9-18 VDC
IGM-HXII33TM-B	V.34, 33.6K, -40 +85C, 18-36 VDC
IGM-HXII33TM-C	V.34, 33.6K, -40 +85C, 36-72 VDC
IGM-HXII56TM	V.92, SERIAL 56K, -40 +85C, 5 VDC
IGM-HXII56TM-A	V.92, SERIAL 56K, -40 +85C, 9-18 VDC
IGM-HXII56TM-B	V.92, SERIAL 56K, -40 +85C, 18-36 VDC
IGM-HXII56TM-C	V.92, SERIAL 56K, -40 +85C, 36-72 VDC

### WARRANTY

Raymar-Telenetics manufactured products are warranted against defects in hardware material and workmanship under normal use for one (1) year from date of original retail purchase. Defective product will be repaired or replaced, determination to be made by Raymar-Telenetics, at no charge. Repaired or replaced products are warranted for 90 days or for original warranty period, whichever is longer. Warranty extends to original end-user only.



Manufactured in the USA by RAYMAR-TELENETICS

Raymar Information Technology, Inc., 7325 Roseville Road, Sacramento, CA 95842  
1-800-695-1951 fax +1-916-783-1952 sales@raymarinc.com www.raymarinc.com  
Service Support Hotline 1-800-747-1522